NSN 5935-00-819-6280

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-819-6280

Thread Class: 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 1.540 inches and 1.580 inches **Overall Height:** Between 0.840 inches and 0.880 inches **Overall Width:** Between 0.420 inches and 0.460 inches **Distance Between Mounting Facility Centers:** Between 1.245 inches and 1.255 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 20 20-20 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket Thread Length: 0.260 inches **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Insert Material Specification:** Mil-m-18794, type sdi-5 military specification single material response single mating end

NSN 5935-00-819-6280

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Quantity:
----------	---------	-----------

20 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.020 gold grains, troy and 0.020 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-18794 spec.