Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-819-6957

	<b>.</b> .
Thread	Class:

2a

**Thread Direction:** 

Right-hand

### **Body Style:**

Straight shape, latching

### **Overall Length:**

0.750 inches

### **Bushing Diameter:**

0.515 inches

**Overall Width:** 

### 0.765 inches

Diameter:

### 0.656 inches

### **Threaded Device Type:**

## Mounting bushing

### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

Mh-7 single mating end

## Contact Removability:

Nonremovable single mating end single contact grouping

## Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

### **Polarization Method:**

Contact

### **Connector Locking Method:**

Latch

### Thready Qty Per Inch (tpi):

20

# Thread Size:

0.500 inches

# **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Insert Material:

Plastic melamine single mating end

# **Terminal Type:**

Solder well single mating end single contact grouping

AeroBase Group

**Insert Material Specification:** Mil-m-14, ty mme military specification single material response single mating end **Included Contact Quantity:** 7 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.007 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-m-14 spec.