## NSN 5935-00-819-6959

**Thread Class:** 

Right-hand **Body Style:** 

0.500 inchesOverall Width:0.766 inches

**Thread Direction:** 

Straight shape, latching **Bushing Diameter:** 

2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-819-6959

Diameter:
0.656 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Mh-5 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Contact
Connector Locking Method:
Latching ring
Thready Qty Per Inch (tpi):
20
Thread Size:
0.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic melamine single mating end
Terminal Type:
Solder well single mating end single contact grouping
Insert Material Specification:
Mil-m-14, ty mme military specification single material response single mating end

## NSN 5935-00-819-6959

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
5 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fila:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):