

View Online at <https://aerobasegroup.com/nsn/5935-00-820-0125>

**Body Material:**

Plastic

**Fabrication Method:**

Molded

**Mounting Hole Style:**

Round, body

**Specific Equipment Accommodated:**

Electron tube

**Contact Material:**

Copper alloy

**Contact Surface Treatment:**

Silver

**Accommodated Contact Quantity:**

5

**Capacitance In Picofarads:**

100.0

**Missing Contact Designation:**

1st contact position and 4th contact position and 6th contact position

**Component Shield Mounting Method:**

Screw

**Polarization Type:**

Center key hole

**Capacitor Quantity:**

1

**Capacitor Location:**

2nd contact position

**Mounting Method:**

Saddle

**Mounting Type For Which Designed:**

Chassis

**Features Provided:**

Center shield

**Contact Position Arrangement Style:**

Octal .687 inch

**Contact Maximum Voltage In Volts And Current Type:**

300.0 ac and 300.0 dc

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.025 silver grains, troy

**Precious Material:**

Silver

**Terminal Type And Quantity:**

5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02300