

View Online at <https://aerobasegroup.com/nsn/5935-00-821-5012>

Overall Length:

2.312 inches

Overall Height:

Between 1.058 inches and 1.178 inches

Overall Width:

1.125 inches

Environmental Protection:

Vibration proof

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Distance Between Mounting Facility Centers:

2.062 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

22-7 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end 3rd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end all contact groupings

Polarization Method:

Mating end

Shell Type:

Solid

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end 1st contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

22 single mating end 3rd contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.025 gold grains, troy and 0.025 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0