

View Online at <https://aerobasegroup.com/nsn/5935-00-821-7728>

**Body Style:**

Straight shape, internal coupling w/backshell

**Overall Length:**

1.690 inches

**Overall Diameter:**

1.082 inches

**Environmental Protection:**

Moisture resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

14-9 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end single contact grouping

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet slot

**Terminal Location:**

Back single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Anodize

**Shell Surface Treatment Specification:**

Mil-a-8625a military specification single treatment response

**Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

**Included Contact Quantity:**

9 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

Face seal-neoprene rubber per mil-r-3065; connector locking method spring loaded coupling ring in bayonet slot

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.