

View Online at <https://aerobasegroup.com/nsn/5935-00-821-7732>

Body Style:

Straight shape, external coupling

Overall Length:

0.835 inches

Overall Height:

1.562 inches

Overall Width:

1.562 inches

Environmental Protection:

Moisture proof

Unthreaded Mounting Hole Diameter:

0.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Distance From Mounting Shoulder To Front Face:

0.562 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

22-69 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

5.0 single mating end 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end all contact groupings

Polarization Method:

Contact

Shell Type:

Solid

Connector Locking Method:

Spring friction

Terminal Location:

Back single mating end all contact groupings

Insert Material:

Plastic phenolic single mating end

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8265a military specification single treatment response

Insert Material Specification:

Mil-p-79, form tr, type pbm military specification single material response single mating end

Included Contact Quantity:

40 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Special Features:

Face seal- neoprene rubber per mil-r-3065

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-79 spec.