Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-822-6526

····· · ······························
Body Style:
Straight edge type
Overall Length:
6.479 inches
Overall Height:
0.636 inches
Overall Width:
0.443 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Distance Between Mounting Facility Centers:
6.219 inches
Board Accommodated Length:
5.766 inches single board
Board Accommodated Width:
Between 0.054 inches and 0.071 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of independent contacts inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
10.0 single mating end single contact grouping
Polarization Method:
Inter-contact polarizing keys
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Contact Material Specification:
Qq-c-530, comp a federal specification single material response single mating end single contact grouping
Insert Material Specification:
Mil-m-19833, type gdi-30 military specification single material response single mating end
Included Contact Quantity:
72 single meting and single contact grouping

72 single mating end single contact grouping



Included Contact Type:

Bifurcated spring single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.