Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-822-7083

| view Online at https://defobasegroup.com/nsi//3303-00-022-/000 |
|---|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape |
| Overall Length: |
| 0.875 inches |
| Overall Height: |
| 0.484 inches |
| Overall Width: |
| 0.250 inches |
| Distance Between Mounting Facility Centers: |
| 0.625 inches |
| Threaded Device Type: |
| Mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 3.0 single mating end single contact grouping |
| Polarization Method: |
| Guide pin/socket |
| Thread Length: |
| 0.141 inches |
| Thready Qty Per Inch (tpi): |
| 56 |
| Thread Size: |
| 0.086 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Insert Material: |
| Plastic melamine mineral filled single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Included Contact Quantity: |
| 14 single mating end single contact grouping |

NSN 5935-00-822-7083

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.014 gold grains, troy and 0.014 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0