NSN 5935-00-823-0700

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-823-0700 **Thread Class:** 2g **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling strain relief **Overall Length:** 2.703 inches **Overall Height:** 1.750 inches **Overall Width:** 1.750 inches **Unthreaded Mounting Hole Diameter:** 0.171 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.375 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.375 inches **Cable Entrance Diameter:** 0.790 inches **Distance From Mounting Shoulder To Front Face:** 1.005 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 12-317 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid

Connector Locking Method:

Externally threaded shell

NSN 5935-00-823-0700

Electrical Receptacle Connector - Page 2 of 2



Connector Cable Strain Relief Method:
Compression nut
Thready Qty Per Inch (tpi):
4
Thread Size:
1.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
10 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0