Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-823-0700

Thread Class:
2g
-9 Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling strain relief
Overall Length:
2.703 inches
Overall Height:
1.750 inches
Overall Width:
1.750 inches
Unthreaded Mounting Hole Diameter:
0.171 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.375 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.375 inches
Cable Entrance Diameter:
0.790 inches
Distance From Mounting Shoulder To Front Face:
1.005 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
12-317 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Externally theaded shell

4

N/a

--

No



**Connector Cable Strain Relief Method:** Compression nut Thready Qty Per Inch (tpi): **Thread Size:** 1.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Anodize **Included Contact Quantity:** 10 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Thread Series Designator:** Acme Shelf Life: Unit Of Measure: **Demilitarization:** Fiig: A039b0