## NSN 5935-00-823-4412

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-823-4412 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.531 inches **Overall Height:** 1.625 inches **Overall Width:** 1.625 inches **Unthreaded Mounting Hole Diameter:** Between 0.145 inches and 0.151 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.245 inches and 1.255 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:** Between 1.245 inches and 1.255 inches **Distance From Mounting Shoulder To Front Face:** Between 0.812 inches and 0.822 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 24-22 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 46.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type:

Solid

**Connector Locking Method:** 

Externally threaded shell

## NSN 5935-00-823-4412

Electrical Receptacle Connector - Page 2 of 2



Thread Length:
0.625 inches
Thread Size:
1.375 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.004 gold grains, troy and 0.004 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0