

View Online at <https://aerobasegroup.com/nsn/5935-00-823-4713>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, flange mount

**Bushing Diameter:**

0.250 inches

**Overall Height:**

0.891 inches

**Environmental Protection:**

Corrosion resistant and moisture resistant and shock resistant and vibration resistant

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nonstd single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.250 inches

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 ty ii military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Gold and silver

**Shell Surface Treatment Specification:**

Mil-g-45204 ty ii military specification 1st treatment response and qq-s-365 federal specification 2nd treatment response

**Shell Material Specification:**

Qq-b-626 comp 22, 1/2 hard federal specification single material response

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Contact and shell surfaces gold and contact and shell surfaces silver

**Precious Material And Weight:**

0.105 gold grains, troy and 0.105 silver grains, troy

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.