NSN 5935-00-823-4962

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-823-4962 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 0.875 inches **Overall Height:** Between 0.450 inches and 0.460 inches **Overall Width:** Between 0.330 inches and 0.340 inches **Distance Between Mounting Facility Centers:** Between 0.620 inches and 0.630 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 11 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Friction Thready Qty Per Inch (tpi): 56 Thread Size: 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate glass filled single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type ii, class 1 military specification single treatment response single mating end single contact grouping **Terminal Type:**

Pin single mating end single contact grouping

NSN 5935-00-823-4962

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

Included Contact Quantity:

11 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.011 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.