NSN 5935-00-824-6166

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-824-6166

TI 101
Thread Class:
2b and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Angle shape, external/internal coupling
Overall Length:
1.810 inches
Overall Height:
1.965 inches
Overall Width:
1.760 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
2
Contact Position Arrangement Style:
Nonstd all mating ends
Contact Removability:
Nonremovable all mating ends single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded shell and externally threaded shell
Thready Qty Per Inch (tpi):
32 and 20
Thread Size:
1.500 inches and 0.750 inches
Contact Material:
Copper alloy all mating ends single contact grouping
Contact Surface Treatment:
Silver all mating ends single contact grouping
Insert Material:
Plastic polytetrafluoroethylene all mating ends
Contact Surface Treatment Specification:
Qq-s-365, ty ii, gr a federal specification single treatment response all mating ends single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response all mating ends single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Silver

NSN 5935-00-824-6166

Connector Adapter - Page 2 of 2



Shell Surface Treatment Specification:

Qq-s-365, type ii, gr a federal specification single treatment response

Shell Material Specification:

Qq-b-626 federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response all mating ends

Included Contact Quantity:

1 2nd mating end single contact grouping

Included Contact Type:

Coaxial socket 2nd mating end single contact grouping

Precious Material And Location:

Contact and body surfaces silver

Precious Material And Weight:

0.110 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unf and unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19468 spec.