

View Online at <https://aerobasegroup.com/nsn/5935-00-824-7588>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

Between 1.224 inches and 1.244 inches

**Overall Diameter:**

0.625 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Nonstd 2nd mating end

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

36 and 24

**Thread Size:**

0.250 inches and 0.625 inches

**Contact Material:**

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:**

Gold all mating ends all contact groupings

**Insert Material:**

Plastic tetrafluoroethylene all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 2 military specification single treatment response all mating ends all contact groupings

**Shell Material:**

Copper alloy

**Included Contact Quantity:**

1 2nd mating end all contact groupings

**Included Contact Type:**

Coaxial socket all mating ends all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.