

View Online at <https://aerobasegroup.com/nsn/5935-00-824-9653>

**Thread Class:**

2a and 2b and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape

**Overall Length:**

1.480 inches

**Overall Height:**

Between 0.950 inches and 0.990 inches

**Overall Width:**

0.665 inches

**Distance Between Mounting Facility Centers:**

Between 0.934 inches and 0.940 inches

**Threaded Device Type:**

Coupling facility and mounting stud

**Mating End Quantity:**

15

**Contact Position Arrangement Style:**

14 single mating end

**Polarization Method:**

Jackscrew and polarization boss

**Shell Type:**

Solid

**Connector Locking Method:**

Jackscrew-socket and friction

**Thread Size:**

0.138 inches and 0.138 inches and 0.138 inches

**Insert Material:**

Plastic diallyl phthalate single mating end and silicon single mating end

**Shell Material:**

Aluminum alloy and cadmium

**Shell Surface Treatment:**

Anodize or cadmium

**Shell Surface Treatment Specification:**

Mil-a-8625, type 1 or type 2 military specification single treatment response

**Insert Material Specification:**

Mil-p-19833, type gdi-30f military specification single material response single mating end

**Thread Series Designator:**

Unc and unc and unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-p-19833 spec.