Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-825-3657

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
Between 0.985 inches and 1.015 inches
Overall Height:
Between 0.450 inches and 0.460 inches
Overall Width:
Between 0.330 inches and 0.340 inches
Environmental Protection:
Moisture resistant and shock resistant and vibration resistant
Distance Between Mounting Facility Centers:
Between 0.745 inches and 0.755 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
14 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Contact
Connector Locking Method:
Friction
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end and glass fiber single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping



Terminal Type:
Pin single mating end single contact grouping
Insert Material Specification:
Mil-m-19833, ty gdi-30 military specification all material responses single mating end
Included Contact Quantity:
14 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.014 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.