Electrical Receptacle Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-00-825-5570

| Thread Class   |
|--|
| Thread Class:<br>2a  |
| Za<br>Thread Direction:  |
|  |
| Right-hand   |
| Overall Length:  |
| 1.313 inches   |
| Overall Diameter:  |
| 0.750 inches   |
| Threaded Device Type:  |
| Mounting bushing   |
| Mating End Quantity:   |
| 1  |
| Contact Removability:  |
| Nonremovable single mating end single contact grouping         |
| Connector Locking Method:                                      |
| Bayonet latch  |
| Radio Frequency Type Contact Characteristic Impedance In Ohms: |
| 50.0 single mating end single contact grouping                 |
| Thready Qty Per Inch (tpi):                                    |
| 24   |
| Thread Size:   |
| 0.313 inches   |
| Insert Material:   |
| Plastic single mating end                                      |
| Shell Material:  |
| Copper alloy   |
| Included Contact Quantity:                                     |
| 1 single mating end single contact grouping                    |
| Bushing Accommodation Hole Shape:                              |
| Round  |
| Included Contact Type:   |
| Coaxial pin single mating end single contact grouping          |
| Thread Series Designator:                                      |
| Unf  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| Fiig:<br>A039b0  |
|  |
|  |