NSN 5935-00-825-7895

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-825-7895 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Angle shape w/cable clamp **Overall Diameter:** 1.461 inches **Body Angle In Deg:** 45.0 **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Cable Entrance Diameter:** Between 0.445 inches and 0.750 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 20-4 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 41.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 250.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring **Distance From Centerline To Connector End:**

Connector Cable Strain Relief Method: Cable clamp 2.797 inches **Distance From Centerline To Cable End:** 2.053 inches

NSN 5935-00-825-7895

Electrical Plug Connector - Page 2 of 2



Thready Qty Per Inch (tpi):	
18	
Thread Size:	
1.250 inches	
Terminal Location:	
Back single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping and nickel single mating end single contact grouping	
nsert Material:	
Rubber single mating end	
Terminal Type:	
Solder well single mating end single contact grouping	
Shell Material:	
Aluminum alloy	
Shell Surface Treatment:	
Cadmium	
Shell Surface Treatment Specification:	
Qq-p-416, type 2, cl 3 federal specification single treatment response	
ncluded Contact Quantity:	
4 single mating end single contact grouping	
ncluded Contact Type:	
Round socket single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.020 gold grains, troy	
Precious Material:	
Gold	
Thread Series Designator:	
Jnef	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Filg:	
4039b0	