Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-825-8107

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Angle shape w/cable clamp
Overall Diameter:
2.463 inches
Body Angle In Deg:
45.0
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Cable Entrance Diameter:
Between 0.922 inches and 1.375 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
36-8 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
41.0 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
1250.0 single mating end all contact groupings
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
280.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp
Distance From Centerline To Connector End:
3.585 inches
Distance From Centerline To Cable End:
3.126 inches
0.120 III01165

NSN 5935-00-825-8107

Electrical Plug Connector - Page 2 of 2



Thready Qty Per Inch (tpi):

16

Thread Size:

2.250 inches

Terminal Location:

Back single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and nickel single mating end all contact groupings

Insert Material:

Rubber single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

46 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.051 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0