

View Online at <https://aerobasegroup.com/nsn/5935-00-825-8146>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

Between 1.984 inches and 2.078 inches

Overall Diameter:

1.812 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Fk-g5c single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

10.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.438 inches

Features Provided:

Pre-tinned terminal

Thready Qty Per Inch (tpi):

18 and 6

Thread Size:

1.438 inches and 1.812 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping or silver single mating end single contact grouping

Insert Material:

Plastic melamine single mating end or plastic phenolic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping or qq-s-365 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

5 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Special Features:

Aluminum insulator grounded to shell for rg-7/u cable

Precious Material And Location:

Contact surfaces gold or contact surfaces silver

Precious Material And Weight:

0.005 gold grains, troy or 0.005 silver grains, troy

Precious Material:

Gold or silver

Thread Series Designator:

Unef and special acme

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.