NSN 5935-00-825-9016

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-825-9016

Body Style:

Straight shape, internal coupling w/strain relief

Body Length:

Between 1.751 inches and 1.771 inches

Overall Diameter:

0.750 inches

Cable Entrance Diameter:

Between 0.115 inches and 0.135 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Tellurium single mating end single contact grouping and copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Rubber single mating end

Contact Surface Treatment Specification:

Qq-s-365 federal specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-f-14072 finish e 516 military specification single treatment response

NSN 5935-00-825-9016

Electrical Plug Connector - Page 2 of 2



Shell Material Specification:

Qq-a-367c comp c or 11, qq-a-270, qq-a-325a or ww-t-789a federal specification single material response

Insert Material Specification:

Mil-r-3065, cl sc 717 a, b, e or f hardness 65 to 85 military specification single material response single mating end

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-r-3065 spec.