NSN 5935-00-825-9086

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-825-9086

Thread Class: 2a and 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling w/backshell **Overall Length:** Between 1.903 inches and 1.973 inches **Overall Diameter:** 1.354 inches **Environmental Protection:** Vibration resistant and heat resistant **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 18-11 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 23.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Internally threaded coupling ring **Operating Tempurature Rating:** 450.0 degrees fahrenheit Thready Qty Per Inch (tpi): 20 and 18 **Thread Size:** 1.000 inches and 1.125 inches **Terminal Location:**

Back single mating end single contact grouping

NSN 5935-00-825-9086

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Plug Connector - Page 2 of 2



| Contact Material: |
|--|
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Rubber single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping |
| Crimping Tool Identifying Number: |
| 77820-ms3191-1 |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Stainless steel |
| Included Contact Quantity: |
| 5 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.005 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unef and unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |