

View Online at <https://aerobasegroup.com/nsn/5935-00-826-0012>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape w/cable clamp

Overall Length:

1.562 inches

Bushing Diameter:

0.625 inches

Overall Height:

Between 0.985 inches and 1.015 inches

Overall Width:

Between 0.985 inches and 1.015 inches

Unthreaded Mounting Hole Diameter:

0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.718 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.718 inches

Cable Entrance Diameter:

0.531 inches

Distance From Mounting Shoulder To Front Face:

Between 0.641 inches and 0.671 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

N single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1500.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver and copper

Shell Surface Treatment Specification:

Qq-s-365 federal specification 1st treatment response

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold and body surface silver

Precious Material And Weight:

0.005 gold grains, troy and 0.100 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.