NSN 5935-00-826-1751

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-826-1751

Body Style:

Straight shape threaded

Overall Length:

0.835 inches

Overall Diameter:

1.108 inches

Environmental Protection:

Vibration resistant and hermetic

Distance From Mounting Shoulder To Front Face:

0.416 inches

Mating End Quantity:

.

Contact Position Arrangement Style:

16-8 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1250.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Nickel single mating end single contact grouping

Contact Surface Treatment:

Tin single mating end single contact grouping

Insert Material:

Glass single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

NSN 5935-00-826-1751

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Chromate
Included Contact Quantity:
8 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Solder flange mounting
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0