Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-826-1811

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Thru-hole mount w/lockin
Overall Length:
0.750 inches
Bushing Diameter:
0.375 inches
Overall Diameter:
0.656 inches
Environmental Protection:
Salt water resistant
Distance From Mounting Shoulder To Rear Face:
0.562 inches
Mounting Facility Thickness:
0.250 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
I
Contact Position Arrangement Style
Contact Position Arrangement Style:
Wk-1 single mating end
Wk-1 single mating end Contact Removability:
Wk-1 single mating end Contact Removability: Nonremovable single mating end single contact grouping
Wk-1 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps:
 Wk-1 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping
 Wk-1 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method:
 Wk-1 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Contact
 Wk-1 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Contact Shell Type:
 Wk-1 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Contact Shell Type: Solid
 Wk-1 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Contact Shell Type: Solid Connector Locking Method:
 Wk-1 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Contact Shell Type: Solid Connector Locking Method: Latching ring
 Wk-1 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Contact Shell Type: Solid Connector Locking Method: Latching ring Thread Length:
 Wk-1 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Contact Shell Type: Solid Connector Locking Method: Latching ring Thread Length: 0.250 inches
 Wk-1 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Contact Shell Type: Solid Connector Locking Method: Latching ring Thread Length: 0.250 inches Thread Size:
Wk-1 single mating endContact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:7.5 single mating end single contact groupingPolarization Method:ContactShell Type:SolidConnector Locking Method:Latching ringThread Length:0.250 inchesThread Size:0.375 inches
Wk-1 single mating endContact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:7.5 single mating end single contact groupingPolarization Method:ContactSolidConnector Locking Method:Latching ringThread Length:0.250 inchesThread Size:0.375 inchesTerminal Location:
Wk-1 single mating endContact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:7.5 single mating end single contact groupingPolarization Method:ContactShell Type:SolidConnector Locking Method:Latching ringThread Length:0.250 inchesThread Size:0.375 inchesTerminal Location:Back single mating end single contact grouping
Wk-1 single mating endContact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:7.5 single mating end single contact groupingPolarization Method:ContactSolidConnector Locking Method:Latching ringThread Length:0.250 inchesThread Size:0.375 inchesTerminal Location:



Contact Surface Treatment: Gold single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Solder well single mating end single contact grouping Shell Material: Plastic **Included Contact Quantity:** 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round keyed **Included Contact Type:** Round socket single mating end single contact grouping **Special Features:** Minature, high voltage **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0