NSN 5935-00-826-2405

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-826-2405

Body Style: Right angle type **Overall Length:** 1.190 inches **Overall Height:** 0.500 inches **Overall Width:** 0.338 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and vibration resistant **Distance Between Mounting Facility Centers:** 1.050 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Connector Locking Method:** Friction **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Glass fiber single mating end and plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification 1st treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** Qq-b-750, comp a federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14, ty sdg-f military specification all material responses single mating end **Included Contact Quantity:** 16 single mating end single contact grouping **Included Contact Type:** Hermaphrodite single mating end single contact grouping

NSN 5935-00-826-2405

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.016 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.