## NSN 5935-00-826-2423

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-826-2423

**Body Style:** Straight edge type w/card guide **Overall Length:** 5.550 inches **Overall Height:** 1.062 inches **Overall Width:** 0.453 inches **Unthreaded Mounting Hole Diameter:** 0.128 inches **Distance Between Mounting Facility Centers:** 5.280 inches **Board Accommodated Length:** 5.010 inches single board **Board Accommodated Width:** 0.074 inches **Mating End Quantity:** 1 **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping **Insert Material Specification:** Mil-m-14, type sdg-f military specification single material response single mating end **Included Contact Quantity:** 

24 single mating end single contact grouping

**Included Contact Type:** 

Hermaphrodite single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

## NSN 5935-00-826-2423

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Weight:</b>
0.031 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.