

View Online at <https://aerobasegroup.com/nsn/5935-00-826-2450>

Body Style:

Straight edge type

Overall Length:

Between 2.095 inches and 2.105 inches

Overall Height:

0.624 inches

Overall Width:

Between 0.355 inches and 0.365 inches

Unthreaded Mounting Hole Diameter:

Between 0.174 inches and 0.178 inches

Distance Between Mounting Facility Centers:

Between 1.795 inches and 1.805 inches

Board Accommodated Width:

Between 0.098 inches and 0.102 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Contact

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45024 type 2 class 1 military specification 1st treatment response single mating end single contact grouping and qq-s-365 type 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-750, comp a, spring federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdi-5 military specification single material response single mating end

Included Contact Quantity:

15 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45024 spec.