

NSN 5935-00-826-3171 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-826-3171 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, latching **Overall Length:** 0.530 inches Diameter: 0.562 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** Mh-9 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Contact Shell Type: Solid **Connector Locking Method:** Snap ring Thready Qty Per Inch (tpi): 20

**Thread Size:** 0.500 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

**Included Contact Quantity:** 

9 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round

## NSN 5935-00-826-3171

A039b0

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.009 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
81349-mil-c-28748 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: