## NSN 5935-00-826-3370

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-826-3370

**Body Style:** Straight shape, internal coupling Overall Length: 1.500 inches **Overall Diameter:** 1.156 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Mating End Quantity: Contact Position Arrangement Style:** 14-5 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1000.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 92.0 Shell Type: Potting **Connector Locking Method:** Bayonet latch **Connector Cable Strain Relief Method:** Potting type **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium

**Shell Surface Treatment Specification:** 

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Included Contact Quantity:** 

5 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

## NSN 5935-00-826-3370

Mil-c-26482 spec.

Electrical Plug Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.025 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-26482 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):