

View Online at <https://aerobasegroup.com/nsn/5935-00-826-7832>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape threaded

Overall Length:

0.656 inches

Overall Diameter:

1.000 inches

Environmental Protection:

Hermetic

Distance From Mounting Shoulder To Front Face:

0.593 inches

Mounting Facility Thickness:

0.125 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

13-12 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

6 and 20

Thread Size:

0.812 inches and 0.875 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Steel single mating end single contact grouping

Contact Surface Treatment:

Cadmium single mating end single contact grouping and tin single mating end single contact grouping

Insert Material:

Glass single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Steel

Shell Surface Treatment:

Cadmium and tin

Included Contact Quantity:

12 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Hermetically sealed

Thread Series Designator:

Special acme and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0