Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-826-8817

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Angle shape w/cable clamp
Overall Diameter:
1.968 inches
Body Angle In Deg:
45.0
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Cable Entrance Diameter:
Between 0.611 inches and 0.938 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
28-12 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
180.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp
Distance From Centerline To Connector End:
3.048 inches
Distance From Centerline To Cable End:
2.376 inches

# NSN 5935-00-826-8817

Electrical Plug Connector - Page 2 of 2



Thready Qty Per Inch (tpi):

18

#### **Thread Size:**

1.750 inches

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Rubber single mating end

## **Terminal Type:**

Solder well single mating end single contact grouping

## Shell Material:

Aluminum alloy

## Shell Surface Treatment:

Cadmium

# Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

#### **Included Contact Quantity:**

26 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

# **Precious Material And Location:**

Contract surfaces gold

# **Precious Material And Weight:**

0.026 gold grains, troy

#### Precious Material:

Gold

# Thread Series Designator:

Uns

# Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A039b0