## NSN 5935-00-826-8909

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-826-8909

**Body Style:** 

Straight edge type

**Overall Length:** 

Between 3.118 inches and 3.132 inches

**Overall Width:** 

Between 0.317 inches and 0.327 inches

**Environmental Protection:** 

Humidity resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

0.190 inches

**Distance Between Mounting Facility Centers:** 

2.803 inches

**Board Accommodated Width:** 

0.200 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

74 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Pin single mating end single contact grouping

**Contact Material Specification:** 

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, type mdg military specification single material response single mating end

**Included Contact Quantity:** 

74 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

## NSN 5935-00-826-8909

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.074 gold grains, troy and 0.074 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.