# NSN 5935-00-826-8950

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-826-8950

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Right angle type
Overall Length:
4.300 inches
Overall Width:
0.360 inches
Body Height:
0.360 inches
Environmental Protection:
Corrosion resistant and vibration resistant and humidity resistant
Distance Between Mounting Facility Centers:
4.000 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper alloy single mating end single contact grouping
Insert Material:
Plastic single mating end

# NSN 5935-00-826-8950

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

#### **Terminal Type:**

Pin single mating end single contact grouping

#### **Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping

#### **Unable To Decode:**

Unable to decode and unable to decode

#### **Included Contact Quantity:**

37 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.011 gold grains, troy

#### **Precious Material:**

Gold

#### **Thread Series Designator:**

Unc

#### Shelf Life:

N/a

### **Unit Of Measure:**

--

# Demilitarization:

No

# Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.