NSN 5935-00-826-8954

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-826-8954

Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape
Overall Length:
4.100 inches
Overall Height:
0.720 inches
Overall Width:
0.710 inches
Environmental Protection:
Humidity resistant and vibration resistant and salt water resistant
Distance Between Mounting Facility Centers:
3.700 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Jackscrew
Thready Qty Per Inch (tpi):
40 and 40 and 40
Thread Size:
0.112 inches and 0.112 inches and 0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal

Terminal Type:

Solder well single mating end single contact grouping

specification 2nd treatment response single mating end single contact grouping

NSN 5935-00-826-8954

Electrical Receptacle Connector - Page 2 of 2



Contact Material Specification:

Qq-b-626, comp 22, half hard federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-19833, ty gdi-30 military specification single material response single mating end

Included Contact Quantity:

50 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.050 gold grains, troy and 0.050 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.