## NSN 5935-00-826-9911

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-826-9911 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.250 inches **Overall Height:** Between 3.859 inches and 3.891 inches **Overall Width:** Between 1.984 inches and 2.016 inches **Unthreaded Mounting Hole Diameter:** 0.150 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 3.490 inches and 3.510 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.865 inches and 0.885 inches **Distance From Mounting Shoulder To Front Face:** Between 0.624 inches and 0.688 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 104 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Polarization Method:** Jackscrew and shell **Shell Type:** Potting **Connector Locking Method:** Jackscrew-socket **Connector Cable Strain Relief Method:** Potting type

**Operating Tempurature Rating:** 

Between -55.0 degrees celsius and 135.0 degrees celsius

Thready Qty Per Inch (tpi):

32

## NSN 5935-00-826-9911

Mil-m-19833 spec.

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
0.164 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Stainless steel
Insert Material Specification:
Mil-m-19833, type gdi-30 military specification single material response single mating end
Shell Guide Type And Location Designator:
B slot
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
104 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Jackscrew type-male and location-right handandjackscrew type-female and location-left hand
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.104 gold grains, troy and 0.104 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):