

View Online at <https://aerobasegroup.com/nsn/5935-00-827-0212>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape threaded

**Overall Length:**

1.406 inches

**Overall Diameter:**

2.250 inches

**Environmental Protection:**

Watertight

**Mounting Facility Thickness:**

0.312 inches

**Threaded Device Type:**

Coupling facility and mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

28-17 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

22.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

900.0 single mating end 3rd contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end 1st contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

80.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

18 and 18

**Thread Size:**

1.750 inches and 1.438 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Surface Treatment:**

Silver single mating end all contact groupings

**Terminal Type:**

Solder well single mating end all contact groupings

**Shell Material:**

Aluminum

**Shell Surface Treatment:**

Anodize or cadmium

**Included Contact Quantity:**

3 single mating end 3rd contact grouping

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Round pin single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.015 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Uns and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0