Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-827-1336

## **Body Style:**

Straight shape, external coupling

## **Overall Length:**

0.978 inches

# **Overall Height:**

1.141 inches

## **Overall Width:**

1.141 inches

#### **Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

# **Unthreaded Mounting Hole Diameter:**

### 0.120 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

0.906 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.906 inches

## Distance From Mounting Shoulder To Front Face:

Between 0.431 inches and 0.462 inches

# Mating End Quantity:

1

## **Contact Position Arrangement Style:**

14-19 single mating end

# **Contact Removability:**

Nonremovable single mating end single contact grouping

## Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

## **Polarization Method:**

Keyway or multiple keyway

## **Insert Position In Deg:**

0.0

## Shell Type:

Solid

# **Connector Locking Method:**

Bayonet pin

# **Terminal Location:**

Back single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# **Terminal Type:**

Solder well single mating end single contact grouping

# Shell Material:

Aluminum alloy

# NSN 5935-00-827-1336

Electrical Receptacle Connector - Page 2 of 2



## Shell Surface Treatment:

## Cadmium

## Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

## **Included Contact Quantity:**

19 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

## **Precious Material And Location:**

Contact surface gold

## **Precious Material And Weight:**

0.019 gold grains, troy

Precious Material:

Gold

## **Test Data Document:**

81349-milc5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-c-5015 government specification

Shelf Life:

N/a

## Unit Of Measure:

--

## **Demilitarization:**

No

# Fiig:

A039b0