

View Online at <https://aerobasegroup.com/nsn/5935-00-827-3474>

Body Style:

Straight shape w/clamp

Overall Height:

2.066 inches

Overall Diameter:

1.687 inches

Environmental Protection:

Thermal shock resistant and moisture resistant and corrosion resistant

Cable Entrance Diameter:

Between 0.280 inches and 0.555 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

20.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

250.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end all contact groupings

Polarization Method:

Contact

Shell Type:

Armored

Connector Locking Method:

Contact twistlock

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Insert Material:

Plastic single mating end or rubber single mating end

Terminal Type:

Screw w/wire lock single mating end all contact groupings

Shell Material:

Metal

Included Contact Quantity:

1 single mating end 2nd contact grouping

Included Contact Type:

Curved pin single mating end all contact groupings

Color:

Natural

Test Data Document:

81349-mil-c-3767 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-3767/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0