Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-827-8597

····· - ······ - ······ - ··· - ··· - ··· - ··· - ··· - ··· - ·
Thread Class:
2a
Thread Direction:
Left-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.617 inches
Overall Height:
2.500 inches
Overall Width:
2.500 inches
Environmental Protection:
Pressure proof
Unthreaded Mounting Hole Diameter:
0.218 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.933 inches and 1.943 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.933 inches and 1.943 inches
Distance From Mounting Shoulder To Front Face:
0.891 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
36-9 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
73.0 single mating end 2nd contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid



Connector Locking Method: Externally threaded shell **Thread Length:** 0.625 inches Thready Qty Per Inch (tpi): 10 **Thread Size:** 2.250 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Silver single mating end all contact groupings **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize **Included Contact Quantity:** 2 single mating end 2nd contact grouping **Included Contact Type:** Round pin single mating end all contact groupings **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.099 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Double stub Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig:

A039b0