

View Online at <https://aerobasegroup.com/nsn/5935-00-828-0700>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

T-shape

Overall Length:

0.750 inches

Overall Height:

0.641 inches

Overall Width:

0.190 inches

Environmental Protection:

Heat resistant and cold resistant and corrosion resistant and vibration resistant and shock resistant and moisture resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

3

Contact Position Arrangement Style:

Smc all mating ends

Contact Removability:

Removable all mating ends single contact grouping

Contact Maximum Current Rating In Amps:

1.5 all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

300.0 all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Contact Surface Treatment:

Gold all mating ends single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 2 military specification single treatment response all mating ends single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial pin all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.003 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.