NSN 5935-00-828-8038



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-828-8038 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Overall Length:** 1.484 inches **Overall Diameter:** 2.885 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Distance From Mounting Shoulder To Front Face:** Between 1.240 inches and 1.260 inches **Mounting Facility Thickness:** Between 0.094 inches and 0.281 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 36-10 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 280.0 Shell Type: Solid **Connector Locking Method:** Internally threaded shell Thread Length: 0.585 inches Thready Qty Per Inch (tpi):

16 and 10

Thread Size:

2.375 inches and 2.250 inches

NSN 5935-00-828-8038

A039b0

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
48 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold and contact surface silver
Precious Material:
Gold and silver
Thread Series Designator:
Uns and double stub
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig: