NSN 5935-00-828-9603

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-828-9603

Body Style: Straight shape **Overall Length:** Between 1.526 inches and 1.556 inches **Overall Height:** 0.598 inches **Overall Width:** Between 0.479 inches and 0.509 inches **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches **Distance Between Mounting Facility Centers:** Between 1.307 inches and 1.317 inches **Mating End Quantity: Contact Position Arrangement Style:** "2, 15" single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Glass single mating end and plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Steel **Shell Surface Treatment:**

Cadmium and tin

Insert Material Specification:

Mil-p-19833, type gdi-30 military specification all material responses single mating end

NSN 5935-00-828-9603

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Quantity:
----------	---------	-----------

15 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.015 gold grains, troy and 0.015 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.