## NSN 5935-00-829-0713

**Thread Class:** 

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-829-0713

2g **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling strain relief **Overall Length:** 2.703 inches **Overall Height:** 2.250 inches **Overall Width:** 2.250 inches **Environmental Protection:** Moisture resistant **Unthreaded Mounting Hole Diameter:** 0.195 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.687 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.687 inches **Cable Entrance Diameter:** 1.290 inches **Distance From Mounting Shoulder To Front Face:** 1.005 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 16-321 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0

## NSN 5935-00-829-0713

Electrical Receptacle Connector - Page 2 of 2



a
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Connector Cable Strain Relief Method:
Cable clamp
Thready Qty Per Inch (tpi):
18
Thread Size:
2.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Oxide aluminum
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.037 gold grains, troy and 0.037 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A039b0