

View Online at <https://aerobasegroup.com/nsn/5935-00-829-7843>

**Body Material:**

Plastic

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Bottom mount w/molded saddle

**Fabrication Method:**

Molded

**Overall Length:**

Between 1.995 inches and 2.005 inches

**Overall Height:**

Between 0.745 inches and 0.755 inches

**Overall Width:**

Between 1.275 inches and 1.285 inches

**Mounting Hole Diameter:**

0.190 inches

**Body Mounting Hole Accommodation Diameter:**

Between 1.182 inches and 1.192 inches

**Distance Between Mounting Facility Centers:**

Between 1.557 inches and 1.567 inches

**Mounting Hole Style:**

Round, w/two mounting holes

**Specific Equipment Accommodated:**

Relay

**Contact Maximum Current Rating In Amps:**

7.5

**Contact Material:**

Beryllium copper

**Contact Surface Treatment:**

Gold and silver

**Accommodated Contact Quantity:**

20

**Polarization Type:**

Colored dot

**Saddle Material:**

Plastic

**Projection Length Above Mounting Surface:**

Between 0.105 inches and 0.115 inches

**Mounting Method:**

Threaded stud

**Mounting Type For Which Designed:**

Chassis

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Contact Position Arrangement Style:**

Concentric

**Contact Maximum Voltage In Volts And Current Type:**

250.0 ac and 250.0 dc

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.020 gold grains, troy and 0.020 silver grains, troy

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unf

**Furnished Items And Quantity:**

4 screw and 2 flat washer and 2 nut

**Terminal Type And Quantity:**

20 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02300