

View Online at <https://aerobasegroup.com/nsn/5935-00-829-7843>

Body Material:

Plastic

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Bottom mount w/molded saddle

Fabrication Method:

Molded

Overall Length:

Between 1.995 inches and 2.005 inches

Overall Height:

Between 0.745 inches and 0.755 inches

Overall Width:

Between 1.275 inches and 1.285 inches

Mounting Hole Diameter:

0.190 inches

Body Mounting Hole Accommodation Diameter:

Between 1.182 inches and 1.192 inches

Distance Between Mounting Facility Centers:

Between 1.557 inches and 1.567 inches

Mounting Hole Style:

Round, w/two mounting holes

Specific Equipment Accommodated:

Relay

Contact Maximum Current Rating In Amps:

7.5

Contact Material:

Beryllium copper

Contact Surface Treatment:

Gold and silver

Accommodated Contact Quantity:

20

Polarization Type:

Colored dot

Saddle Material:

Plastic

Projection Length Above Mounting Surface:

Between 0.105 inches and 0.115 inches

Mounting Method:

Threaded stud

Mounting Type For Which Designed:

Chassis

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Contact Position Arrangement Style:

Concentric

Contact Maximum Voltage In Volts And Current Type:

250.0 ac and 250.0 dc

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.020 gold grains, troy and 0.020 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unf

Furnished Items And Quantity:

4 screw and 2 flat washer and 2 nut

Terminal Type And Quantity:

20 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02300