NSN 5935-00-830-4826

Body Style:

Hood, side opening, w/clamp

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-830-4826

Overall Length:
4.125 inches
Overall Height:
1.953 inches
Overall Width:
1.250 inches
Environmental Protection:
Vibration resistant
Cable Entrance Diameter:
0.625 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
32 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
800.0 single mating end single contact grouping
Polarization Method:
Polarization Method:
Polarization Method: Shell
Polarization Method: Shell Shell Type:
Polarization Method: Shell Shell Type: Hood, side opening
Polarization Method: Shell Shell Type: Hood, side opening Connector Locking Method:
Polarization Method: Shell Shell Type: Hood, side opening Connector Locking Method: Latch
Polarization Method: Shell Shell Type: Hood, side opening Connector Locking Method: Latch Connector Cable Strain Relief Method:
Polarization Method: Shell Shell Type: Hood, side opening Connector Locking Method: Latch Connector Cable Strain Relief Method: Cable clamp
Polarization Method: Shell Shell Type: Hood, side opening Connector Locking Method: Latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating:
Polarization Method: Shell Shell Type: Hood, side opening Connector Locking Method: Latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius
Polarization Method: Shell Shell Type: Hood, side opening Connector Locking Method: Latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location:
Polarization Method: Shell Shell Type: Hood, side opening Connector Locking Method: Latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping
Polarization Method: Shell Shell Type: Hood, side opening Connector Locking Method: Latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Polarization Method: Shell Shell Type: Hood, side opening Connector Locking Method: Latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Polarization Method: Shell Shell Type: Hood, side opening Connector Locking Method: Latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Polarization Method: Shell Shell Type: Hood, side opening Connector Locking Method: Latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Polarization Method: Shell Shell Type: Hood, side opening Connector Locking Method: Latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:

NSN 5935-00-830-4826Electrical Plug Connector - Page 2 of 2



Shell Material:
Copper alloy
Shell Surface Treatment:
Nickel
Shell Guide Type And Location Designator:
B pin and h pin and 2 pin and 5 pin
Included Contact Quantity:
32 single mating end single contact grouping
Included Contact Type:
Leaf spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.032 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0