NSN 5935-00-830-4839

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-830-4839

| Three of Olegon |
|---|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, internal coupling |
| Overall Length: |
| 1.656 inches |
| Overall Diameter: |
| 1.460 inches |
| Threaded Device Type: |
| Back shell |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 22-7 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet latch |
| Thread Size: |
| 1.438 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Surface Treatment: |
| Cadmium and chromate |
| Shell Surface Treatment Specification: |
| Qq-p-416 federal specification 1st treatment response |
| Included Contact Quantity: |
| 7 single mating end single contact grouping |

NSN 5935-00-830-4839

Electrical Plug Connector - Page 2 of 2



| Included Contact Type: |
|------------------------|
|------------------------|

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold and contact surface silver

Precious Material And Weight:

0.007 gold grains, troy and 0.007 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0